

MAXXFAST Anchor bolt ThruFast - ThruMaxx Steel Zinc plated ETA-7 10X120



Article number 30551.100.120

Brand -

UBB 500577353708

UNSPSC 31162101

EAN 8715494323079

PKG. of 50 Full Box Only

Technical Parameters

Diameter (mm) 10

Info

do = Nominal diameter of drill bit
 s = Width across flats ring $\varnothing$ = Washer diameter
 df = Diameter of clearance hole in the fixture h1 = Recommended drilling depth h(nom) = Minimum hole depth hef = Effective anchorage depth
 Scr,N = Spacing characteristic Ccr,N = Edge distance characteristic
 tfix(max) = Grip range Tinst = Tightening torque in Nm Nrec = Recommended load in kN The allowable load is valid for one single anchor, at non-cracked concrete (pressure zone) with concrete class C20/25, incl. partial safety factor $\gamma_f = 1,4$ and if the

Standards

Scr, N and Ccr,
N are taken in to
account.

Extra info	ETA-7
Material	Steel
Surface treatment	Zinc plated
Thread	Metric thread
Info	Full boxes only.

Technical Specification

C_{cr} , N	83
Diameter (d-D)	M10
d_f	12
d_o	10
h (nom.)	66.5
h_1	75
h_{ef}	55
N_{rec}	6.35
Ring $\varnothing$	20
s	17
S_{cr} , N	165
t_{fix} (max.)	40
T_{inst}	35

Technical Drawing

